

补丁软件 (Patch) 的加载

补丁软件 (Patch) 的下载

1、确保软件 patch 文件已经保存在 “ software ” 或是 (SDS/software) 的路径下，修改文件属性并解压该文件：

```
# cd /software
# umask 22
# tar -xvf frameRelay7T1179A_CF02C.tar
```

2、登录交换机上，将 patch 下载到交换机上 (MSS7K 和 MSS15K)

```
> set sw dld avl ! patch_CF02C
> set sw dld processorTargets ! i960 ppc
> start -h(IP address of SDS site) -u(userID) -p(password) sw dld
```

3、查看当前能激活的 patch 列表

```
> l sw av/patch_CF02C patch/*
Sw Av/PATCH_CF02C Patch/atmNetworkingFT1194A
Sw Av/PATCH_CF02C Patch/baseFR1189A
Sw Av/PATCH_CF02C Patch/baseFR1273A
Sw Av/PATCH_CF02C Patch/frameRelayFT1179A
Sw Av/PATCH_CF02C Patch/ipFT1216A
Sw Av/PATCH_CF02C Patch/networkingFT1284A
Sw Av/PATCH_CF02C Patch/trunksFR1325A
ok                2006-04-19 11:15:53.94
```

4、加载要求的 patch 并激活 patch

```
PROV> set sw avl patch_CF02C
PROV> set sw pa frameRelay7T1179A baseFR1189A baseFR1273A
PROV> check prov
PROV> act prov
PROV> conf prov
PROV> save prov
```